

FV 65 WDM S

A range of powerful vacuum cleaners for dust and liquids, with 2 or 3 two-stage motors, available with a 65-litre plastic or steel tank. These models are easy to move around, thanks to the large handle and the trolley with large rear wheels for stability and pivoted front wheels for enhanced manoeuvrability. A set of professional nozzles is supplied as standard, to meet a variety of cleaning needs, along with a tube to facilitate the drainage of liquids.

The models with a plastic tank are recommended for the construction sector, where large areas are involved and metal, stone and cement waste needs to be collected, as well as for the professional cleaning, car wash and car hire fields.

The models with a steel tank are ideal for the industrial sector and paper mills, for removing the fine dust generated during the processing of the paper. They can even be used in places with a high level of static electricity, counteracting its effect by adding a chain that makes contact with the floor.



A specific hose is provided as standard to enable liquids to be drained off more quickly and easily at the end of the job.

EQUIPMENT	FV 65 WDM S
Accessory kit Ø40	standard
Drainage hose	standard
Microfibre pocket filter	optional
Paper filter bag	optional
Nylon filter	optional
Washable cartridge filter	optional
Cartridge filter	optional
Front squeegee	optional



To increase productivity when removing liquids from the floor, there is an optional fixed front squeegee for picking up the fluids quickly and drying perfectly, thereby optimising work time and costs.



A specific 15-metre vacuum hose can be requested for special needs, for cleaning areas some distance from the vacuum cleaner. It enables the vacuum cleaner to be left outside when cleaning white rooms for instance, or in the agricultural sector to vacuum inside vehicles, leaving the vacuum cleaner on the ground

TECHNICAL DATA		FV P65.2	FV P65.3	FV A65.2	FV A65.3	
		WDM S	WDM S	WDM S	WDM S	
Type of dirt		wet & dry				
Tank material		plastic steel		eel		
Motors		2	3	2	3	
Stages		2				
Power	W	2400	3600	2400	3600	
Vacuum	kPa	22				
Air flow	l/s	108	160	108	160	
Tank volume	I	65 66,5			5,5	
Bag capacity		25				
Power supply	V/Hz	220-240 / 50-60				
Sound pressure level (ISO 11201 – LpA)	dB (A)	72	73	72	73	
Cable length	m	10				
Weight	kg	20	22	20	22	
Machine dimensions (L x h x w)	mm	580 x 950 x 540				

STANDARD EQUIPMENT



Accessory kit Ø40: 2 chromeplated tubes, a hose, a nozzle for liquids, a nozzle with bristles for flooring, a nozzle for crevices, a vacuum brush, a fabric filter and a foam filter.

CERTIFICATIONS



AWARDS



OPTIONAL

For any additional information or for a demo please contact your usual Fimap dealer



FIMAP spa - Via Invalidi del Lavoro, 1 - 37059 S. Maria di Zevio - Verona - Italy Tel. +39 045 6060411 - Fax +39 045 6060417 - E-mail: contact@fimap.com

D in († ¥ 🎯